

# M 015168

# SCHEDA TECNICA

LOC		DIST		REVISIONS				
P	LTR	DESCRIPTION		DATE	DWN	APVD		
M		REDRAWN ET00-0107-04		06MAY2004	AV	CT		
M1		CHANGED Q.TY PER REEL ET00-0050-05		21APR2005	AV	GT		
M2		REVISED PER ECO-10-000445		09JAN10	KK	AEG		

  

Section B-B

1 OTTONE P/N 280919-1  
 BRASS P/N ~~280919-1~~ **OBSELETE** 2  
 OTTONE STAGNATO 280919-2  
 TIN BRASS P/N 280919-2  
 BRONZO FOSF. STAGNATO 280919-4  
 TIN PHOS.BRZ. P/N 280919-4

WIRE RANGE 0.5-1.5 mm<sup>2</sup>  
 INSULATION 2.3-3.3 mm DIA.

2 **OBSELETE PARTS: OBSELETE CIS**  
**STREAMLINING PER D.RENAUD/D.SINISI**

Adatto per linguetta spessore 0.8 mm

DIMENSIONS:		DWN	06MAY2004	MATERIAL		FINISH	-
mm		A. Vecchia		<b>tyco</b> Electronics	tyco Electronics AMP Italia S.p.A. 10093 Collegno TO		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK	06MAY2004				
0 PLC ±0.4		C. Tartari					
1 PLC ++		APVD	06MAY2004				
2 PLC ++		C. Tartari		PRODUCT SPEC			
3 PLC ++				108-20020			
4 PLC ++				NAME: CONTATTO FASTIN-ON FEMMINA SERIE 4.8 mm			
ANGLES ±1°				4.8 mm SERIES FASTIN-ON RECEPTACLE			
				SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
				A4	00779	C=280919	-
				CUSTOMER DRAWING		SCALE	5:1
				SHEET		1	OF
				REV		M2	

