



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 COPYRIGHT ALL RIGHTS RESERVED.

LOC	DIS1	REVISIONS	DATE	ENK	APPO
		DESCRIPTION			
C1		REVISED PER ECO-11-005140	31MAR11	RK	HMR

INSERTO SERRACAVI (CLAMPING INSERT)  
 CORPO CORAZZA (CLAMPING INSERT)  
 #5-20 VITI AUTOFILETTANTI IN ACCIAIO ZINCATO (Q.TA' 2)  
 (#5-20 SELF-TAPPING SCREWS, ZINC PLATED STEEL, Q.TY 2)

Ø 40.65 ± 0.6  
 39.5 ± 0.75

AREA SERRAGGIO CAVI (CLAMPING AREA)

- MATERIALE : TERMOPLASTICO, COLORE NERO  
 (MATERIAL : THERMOPLASTIC, BLACK COLOUR)
- PARTICOLARI FORNITI NON ASSEMBLATI IN SACCHETTO DI PLASTICA  
 (PARTS PACKAGED UNASSEMBLED INTO A PLASTIC BAG)
- L'AREA SERRAGGIO CAVI E' VARIABILE DA 64.5 A 264.5 mm<sup>2</sup>  
 IN FUNZIONE DEL TIPO E POSIZIONE DELL'INSERTO SERRACAVO  
 (CABLE CLAMPING AREA ADJUSTABLE FROM .100 TO .410 SQ. IN.  
 BY SELECTING AND REVERSING CLAMPING INSERTS)
- QUESTO CONNETTORE E' RICONOSCIUTO E CERTIFICATO   
 (THIS CONNECTOR IS UL RECOGNIZED AND CSA CERTIFIED)
- Ø MAX DEL FASCIO CAVI = 17.9 mm.  
 (MAXIMUM CABLE O.D. = .703 IN.)

P/N 182652-1 COME RAPPRESENTATO  
 (P/N 182652-1 AS SHOWN)

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DIN 9135		STE TE Connectivity	
mm		mm		R. FABR. 08/11/11		C.P.C. CABLE CLAMP KIT	
		±0.3		TARTARI		SIZE 23	
MATERIAL		FINISH		APPO 108-10024		DRAWING NO	
				APPLICATION SPEC		A3 00779 ©182652	
				WEIGHT		SCALE 2:1 SHEET OF REV C1	
				CUSTOMER DRAWING			