






M 22902DTM

SCHEDA TECNICA



PLUG HOUSING

REV	DTM06-3S	REVISIONS		
SYM	DESCRIPTION	DATE	APPROVED	
NC	NEW RELEASE PER E.O. A14874	7-21-95	RDR	
A	REDRAWN & REVISED PER E.O. P17172	3-6-01	RDR	

CONTACT SIZE	MIN. INSUL. O.D.	MAX. INSUL. O.D.	WIRE RANGE [mm ²] REF ONLY
20	.053 [1.35]	.120 [3.05]	16-20 AWG [1.0-0.5]

6. MATERIAL - HOUSING: PLASTIC; GROMMET: RUBBER.
5. THIS PLUG MATES WITH DTM04-3P-**** RECEPTACLE. (**** = ALL MODIFICATIONS)
4. FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 0425-015-0000.
3. SECONDARY WEDGE LOCK SOLD SEPARATELY: WM-3S.
2. DIMENSION TOLERANCE: ±.025 [.64].
1. DIMENSIONS ARE IN INCHES [mm].

NOTES: UNLESS OTHERWISE SPECIFIED

SIGNATURE & DATE		PLUG 3 SKT. CONT. #20 DTM SERIES	CP	DATE	
DR	J. APOSTOL 05MAR2001		The Deutsch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92345		
CHK	[Signature]		B DTM06-3S	DWG	CODE
PE	[Signature]			SIZE	(1/13)
APPD	[Signature]	ENVELOPE	SHEET	OF	
SCALE	NONE WT				

