




# M 22904DTM

# SCHEDA TECNICA



REV	DTM06-4S	REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED		
NC	NEW RELEASE PER E.O. A14874	11/21/95	R.D.R.		
A	REVISED & REDRAWN PER E.O. P20071	11-14-08	REV		

CONTACT SIZE	MIN. INSUL. O.D.	MAX. INSUL. O.D.	WIRE RANGE [mm <sup>2</sup> ] REF ONLY
20	.053 [1.35]	.120 [3.05]	16-22 AWG [1.5-0.5]

- 6. MATERIAL - HOUSING: PLASTIC; GROMMET: RUBBER.
- 5. THIS PLUG MATES WITH DTM04-4P-\*\*\*\* RECEPTACLE. (\*\*\*\* = ALL MODIFICATIONS)
- 4. FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 0425-015-0000.
- 3. SECONDARY WEDGE LOCK SOLD SEPARATELY: WM-4S.
- 2. DIMENSIONS TOLERANCE: ±.025 [.64].
- 1. DIMENSIONS ARE IN INCHES [mm].

NOTES: UNLESS OTHERWISE SPECIFIED

SIGNATURE & DATE		PLUG 4 SKT. CONT. #20 COLOR: GREY DTM SERIES	EP	MATL. CODE
DR	R. McCORD 11/13/08		3850 INDUSTRIAL AVE. HEMET, CA 92545	
CHK	[Signature] 11/14/08	ENVELOPE	DEUTSCH INDUSTRIAL	B DTM06-4S
PE	[Signature] 11/14/08			
APPD	[Signature] 11-14-08			
SCALE	NONE WT		CODE 11159	SHEET   OF

