



CONTACT ORIENTATION ON REEL FOR AUTO CRIMP MACHINE

REV E 1062-20-01 \*\*

**SECTION A-A**  
CONDUCTOR WINGS

**SECTION B-B**  
INSULATION WINGS

SYM	DESCRIPTION	DATE	APPROVED
B	REVISED PER E.O. P17937	11-1-02	R.D.R.
C	REVISED PER E.O. P19261	6-13-06	R.D.R.
D	REVISED PER E.O. P19555	6-13-06	R.D.R.
E	REVISED PER E.O. P20392	2-3-09	RDR

Ø .076±.005 TYP [1.93±.12]

Ø .100 TYP [2.54]

20-01 20-01 20-01

ENVELOPE

SIGNATURE & DATE		STAMPED CONTACT SOCKET SIZE 20	EP	MATL. CODE
DR	V. APOSTOL 01DEC2009		3850 INDUSTRIAL AVE. HEMET, CA 92545	
CHK	D. Nay 12/6/09	ENVELOPE	<b>B 1062-20-01 **</b>	
PE	D. Nay 12/6/09		DWG. SIZE	CODE 11139
APPD	R. Rinaldi 12-3-09			
SCALE	NONE			

7. CONTACT BODY MATERIAL: COPPER ALLOY; CONTACT SLEEVE MATERIAL: STAINLESS STEEL.
6. WHEN \*\* = 22 PLATING IS NICKEL.  
    \*\* = 44 PLATING IS GOLD.  
    \*\* = 77 PLATING IS TIN.
5. SEE 0425-015-0000 FOR CONTACT PERFORMANCE AND WIRE APPLICATION CHARACTERISTICS.
4. THIS CONTACT MAY BE CRIMPED WITH DCT20-02-00 AUTOMATIC DIE OR DT1-20-00 HAND TOOL. SEE DRAWING 0425-207-0000 FOR APPLICABLE WIRE SIZE, INSULATION DIAMETER RANGE, AND CRIMPING INFORMATION.
3. ONE REEL CONTAINS APPROXIMATELY 4000 CONTACTS.
2. DIMENSIONAL TOLERANCE: ±.025 [0.63].
1. DIMENSIONS ARE IN INCHES [mm].

NOTES: UNLESS OTHERWISE SPECIFIED

