

M 22915

SCHEDA TECNICA



CONTACT ORIENTATION ON REEL FOR AUTO CRIMP MACHINE

SECTION A-A
CONDUCTOR WINGS

SECTION B-B
INSULATION WINGS

REV	E	1060-20-01 * *	REVISIONS		
SYM	DESCRIPTION	DATE	APPROVED		
B	REVISED PER E.O. P17913	11-1-02	R.D.R.		
C	REVISED PER E.O. P18438	12-19-03	R.D.R.		
D	REVISED PER E.O. P20044	11-3-08	R.D.R.		
E	REVISED PER E.O. P20392	2-3-09	R.D.R.		

7. MATERIAL: COPPER ALLOY.

6. WHEN ** = 22 PLATING IS NICKEL.
 ** = 44 PLATING IS GOLD.
 ** = 77 PLATING IS TIN.

5. SEE 0425-015-0000 FOR CONTACT PERFORMANCE AND WIRE APPLICATION CHARACTERISTICS.

4. THIS CONTACT MAY BE CRIMPED WITH DCT20-02-00 AUTOMATIC DIE OR DTT-20-00 HAND TOOL. SEE DRAWING 0425-207-0000 FOR APPLICABLE WIRE SIZE, INSULATION DIAMETER RANGE, AND CRIMPING INFORMATION.

3. ONE REEL CONTAINS APPROXIMATELY 4000 CONTACTS.

2. DIMENSIONAL TOLERANCE: ±.025 [0.63].

1. DIMENSIONS ARE IN INCHES [mm].

NOTES: UNLESS OTHERWISE SPECIFIED

SIGNATURE & DATE	
DR	J. APOSTOL 01DEC2009
CHK	D. M... 12/2/09
PE	D. M... 12/2/09
APPD	R. K... 12-3-09
SCALE	NONE
WT	

STAMPED CONTACT
PIN
SIZE 20

ENVELOPE

EP	MATL. CODE
3850 INDUSTRIAL AVE. HEMET, CA 92545	
DEUTSCH INDUSTRIAL	
B	1060-20-01 * *
DWG. SIZE	CODE 11139
SHEET	1 OF 1

