



- CONTACT MATERIAL CONTAINS 94% COPPER MINIMUM. CONTACT SLEEVE IS STAINLESS STEEL.
 - WHEN ** = 44 PLATING IS GOLD.
** = 66 PLATING IS TIN/NICKEL.
 - SEE 0425-015-0000 FOR CONTACT PERFORMANCE AND WIRE APPLICATION CHARACTERISTICS.
 - THIS CONTACT MAY BE CRIMPED WITH DCT12-02-00 AUTOMATIC DIE OR DTT-12-00 HAND TOOL. SEE DRAWING 0425-208-0000 FOR APPLICABLE WIRE SIZE, INSULATION DIAMETER RANGE, AND CRIMPING INFORMATION.
 - ONE REEL CONTAINS APPROXIMATELY 2500 CONTACTS.
 - DIMENSION TOLERANCE: $\pm .025$ [$\pm .64$].
 - DIMENSIONS ARE IN INCHES [mm].
- NOTES: UNLESS OTHERWISE SPECIFIED



REV	DESCRIPTION	DATE	APPROVED
C	1062-12-01 **		
NC	NEW RELEASE PER E.O. P15224	02-17-97	R.D.R.
A	REVISED PER E.O. P15646	05-29-98	R.D.R.
B	REVISED PER E.O. P16979	12-08-00	R.D.R.
C	REVISED PER E.O. P19555	7-11-07	RDR

SIGNATURE & DATE		STAMPED CONTACT SOCKET SIZE 12 ENVELOPE	EP	EP058	MAIL CODE	
DR	D. MEYER 11/14/00		The Deutsch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92545			
CHK	[Signature] 7/11/81		B	1062-12-01 **		
PE	[Signature] 1/2/07			CODE	11139	SHEET OF
APPD	R. Rad 7-11-97			DWG SIZE		
SCALE	NONE WT					

