



NOTES

- UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
- WHEN PARTS ARE SHIPPED THEY MUST BE PACKED IN PLASTIC BAGS OR SHIPPING CONTAINERS MUST BE LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID FOREIGN MATTER.
- SEALING CODE 3 - DESIGN WILL PASS SALT FOG AND IMMERSION TEST AFTER CONDITIONING AS SPECIFIED IN S24-710 (METH-PAGE) WHEN MATED TO MATING PART OR EQUIVALENT.
- REFERENCE MATING COMPONENTS OR EQUIVALENT:
TRACTION CONTROL MOTOR/DRIVER 15249737
- THESE PARTS ACCEPT THE FOLLOWING COMPONENTS OR EQUIVALENT:
TERMINAL 12077412 FOR SEALED APPLICATIONS
TERMINAL 12119853 FOR UNSEALED APPLICATIONS
CABLE SEAL 12016203 FOR SEALED APPLICATIONS
CONNECTOR POSITION ASSURANCE LOCK 1
A. IN-LINE APPLICATIONS 12020933
B. TRACTION CONTROL APPLICATIONS 12110292
TERMINAL POSITION ASSURANCE LOCK 1
A. SEALED APPLICATION 12305018
B. UNSEALED APPLICATION 12146475

