

# M 480700

# SCHEDA TECNICA

1. MATE WITH APPROPRIATE UNIVERSAL MATE-IN-LOCK™ CAP OR HEADER.  
 2. SMALL NOTCH ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE RETAIL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS (1.0 LBS). NO INDIVIDUAL NOTCH TOWER SHALL INCREASE THIS FORCE BY OVER 2.2 NEWTONS (0.5 LBS).  
 3. DIMENSION INDICATED IS AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR.  
 4. FOUR PINS EQUALLY SPACED, NO SPECIFIC ORIENTATION, NO PINS OR SIX PINS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL.  
 5. UNDIMENSIONED RECOMMENDED COMPONENT LOAD AND CSA CERTIFICATION LOAD TO BE LOCATED ONCE EACH ON SIDE OF HOUSING.

27.43	1.080
20.32	800
14.73	580
11.68	480
7.62	300
6.35	215
5.13	200
MM	IN

CONVERSION TABLE

BLACK	1-480700-9
GREEN	1-480700-8
RED	1-480700-6
GREEN	1-480700-5
YELLOW	1-480700-4
ORANGE	1-480700-3
RED	1-480700-2
BROWN	1-480700-1
NATURAL	1-480700-0
BLACK	1-480700-0

METRIC



1. STAMP NUMBERS 3.18 HIGH AT WIRE END OF HOUSING (12 POINT DAVID TYPE).  
 2. CHARACTERS TO BE POSITIONED ON HOUSING TO BE READ FROM WIRE END ONLY.  
 3. VIOLET, BLACK, BROWN AND BLUE COLORED BLOCKS TO BE STAMPED WITH WHITE CHARACTERS. ALL OTHER COLORED BLOCKS TO BE STAMPED WITH BLACK CHARACTERS.

6.73	265	-	-
5.97	230	27.43	1.080
3.18	125	20.32	800
0.38	0.15	14.73	580
0.13	0.05	7.62	300
MM	IN	MM	IN

CONVERSION TABLE

NATURAL	2-480700-0
COLOR	PART NUMBER

METRIC

