

M 480704

SCHEDA TECNICA

1. MATE WITH APPROPRIATE UNIVERSAL MATE-PLUG/LET CAP OR READER.

2. SMALL NICKS ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE INITIAL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS (1.0 LBS). NO HOUSING NICKED THERE. SHALL REDUCE THIS FORCE BY OVER 2.2 NEWTONS (0.5 LBS).

3. DIMENSION INDICATED IS AS MOULDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR.

4. FOUR PINS EQUALLY SPACED, NO SPECIFIC ORIENTATION, NO RED OR RED PINS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL.

5. UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ON EACH SIDE OF HOUSING.

6. MANUFACTURING LOCATION ID ON SIDE OF HOUSING (OPTIONAL).

7. TRADEMARK LOCATION (AMP OR TE CONNECTIVITY).

8. OBSOLETE PARTS: OBSOLETE CS STREAMLINED PER D-RINALDI/D-SHRS

27.43	1.080
26.32	800
11.68	460
13.97	550
6.30	250
6.35	254
0.13	0.005
0.15	0.006
0.18	0.007
0.20	0.008
0.25	0.010
0.30	0.012
0.35	0.014
0.40	0.016
0.45	0.018
0.50	0.020
0.55	0.022
0.60	0.024
0.65	0.026
0.70	0.028
0.75	0.030
0.80	0.032
0.85	0.034
0.90	0.036
0.95	0.038
1.00	0.040
1.05	0.042
1.10	0.044
1.15	0.046
1.20	0.048
1.25	0.050
1.30	0.052
1.35	0.054
1.40	0.056
1.45	0.058
1.50	0.060
1.55	0.062
1.60	0.064
1.65	0.066
1.70	0.068
1.75	0.070
1.80	0.072
1.85	0.074
1.90	0.076
1.95	0.078
2.00	0.080
2.05	0.082
2.10	0.084
2.15	0.086
2.20	0.088
2.25	0.090
2.30	0.092
2.35	0.094
2.40	0.096
2.45	0.098
2.50	0.100
2.55	0.102
2.60	0.104
2.65	0.106
2.70	0.108
2.75	0.110
2.80	0.112
2.85	0.114
2.90	0.116
2.95	0.118
3.00	0.120
3.05	0.122
3.10	0.124
3.15	0.126
3.20	0.128
3.25	0.130
3.30	0.132
3.35	0.134
3.40	0.136
3.45	0.138
3.50	0.140
3.55	0.142
3.60	0.144
3.65	0.146
3.70	0.148
3.75	0.150
3.80	0.152
3.85	0.154
3.90	0.156
3.95	0.158
4.00	0.160
4.05	0.162
4.10	0.164
4.15	0.166
4.20	0.168
4.25	0.170
4.30	0.172
4.35	0.174
4.40	0.176
4.45	0.178
4.50	0.180
4.55	0.182
4.60	0.184
4.65	0.186
4.70	0.188
4.75	0.190
4.80	0.192
4.85	0.194
4.90	0.196
4.95	0.198
5.00	0.200

3-DIMENSIONAL MODEL NTS

METRIC

BLACK	1-480704-0
GRAY	1-480704-1
GREEN	1-480704-2
BLUE	1-480704-3
ORANGE	1-480704-4
RED	1-480704-5
YELLOW	1-480704-6
PURPLE	1-480704-7
BROWN	1-480704-8
TEAL	1-480704-9
PINK	1-480704-10
WHITE	1-480704-11
TRANSPARENT	1-480704-12
COLOR	PART NUMBER

TE Connectivity

1. STAMP NUMBERS 3.18 HIGH AT WIRE END OF HOUSING (12 POINT GAUGE TYPE).

2. CHARACTERS TO BE POSITIONED ON HOUSING TO BE READ FROM WIRE END ONLY.

3. TO BE STAMPED WITH WHITE CHARACTERS. ALL OTHER COLORED BLOCKS TO BE STAMPED WITH BLACK CHARACTERS.

3-DIMENSIONAL MODEL NTS

METRIC

NATURAL	2-480704-0
COLOR	PART NUMBER

TE Connectivity

