

M 480705

SCHEDA TECNICA

REV. 00

1. MATE WITH APPROPRIATE UNIVERSAL MATE-IN-LOCK™ PAIR.
 2. RECOMMENDED PANEL THICKNESS 0.76 - 2.29.
 3. PANEL MUST BE PUNCHED SO THAT THE HOUSING ENDS LIKE PANEL IN THE SAME DIRECTION AS THE PUNCH.
 △ OPTIONAL FOR KEYING HOUSING IN PANEL.
 △ CIRCUIT NUMBER 1 LOCATION.
 △ DIMENSION INDICATED IS AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT HEAT TREATMENT ABSORPTION MAY OCCUR.
 △ FOUR RISE SIGNALS SPECIES NO SPECIFIC ORIENTATION AND RISE OR FALL RISE EQUALLY SPECIES NO SPECIFIC ORIENTATION, OPTIONAL.
 △ UNDERWRITERS RECOMMENDED COMPONENT LOAD AND OR CONFIGURATION LOAD TO BE LOCATED ONCE EACH ON SIDE OF HOUSING.
 △ OBSOLETE PARTS: OBSOLETE CIS STREAMLING PER D.RENALDO/2/SING

SEE DETAIL A

DETAIL A
OPTIONAL CONSTRUCTIONS

RECOMMENDED PANEL CUT OUT

3-DIMENSIONAL MODEL
NTS

6.35	250	27.43	1.083
4.70	175	28.13	1.030
2.79	110	28.13	1.030
2.54	100	20.32	800
2.29	90	14.95	585
0.76	0.50	13.97	550
0.76	0.50	12.87	490
0.76	0.10	8.13	320
0.13	0.05	14.95	585
MM	IN	MM	IN

CONVERSION TABLE

BLACK	1-480705-0
GREEN	1-480705-1
RED	1-480705-2
YELLOW	1-480705-3
ORANGE	1-480705-4
BLUE	1-480705-5
NATURAL	1-480705-6
COLORED	1-480705-7
2-PIN PLATELET	1-480705-8

METRIC



REV. 00

1. STAMP NUMBERS 3.18 HIGH AT WIRE END OF HOUSING (12 POINT DAVID TYPE). CLARIFICATION MARKS UNDER THE 6 & 9.
 2. CHARACTERS TO BE STAMPED ON HOUSING IN A MANNER AS TO BE READ FROM WIRE END ONLY.
 3. VIOLET-BLACK/BROWN/LD BLUE COLORED BLOCKS TO BE STAMPED WITH WIRE CHARACTERS. ALL OTHER COLORED BLOCKS TO BE STAMPED WITH BLACK CHARACTERS.

DETAIL A

RECOMMENDED PANEL CUT OUT

3-DIMENSIONAL MODEL
NTS

6.35	250	27.43	1.083
4.70	185	27.43	1.083
3.18	125	28.13	1.030
0.38	0.10	20.32	800
0.38	0.10	13.97	550
0.13	0.05	8.13	320
MM	IN	MM	IN

CONVERSION TABLE

NATURAL	2-480705-0
COLOR	PART NO.
BLACK	1-480705-0
GREEN	1-480705-1
RED	1-480705-2
YELLOW	1-480705-3
ORANGE	1-480705-4
BLUE	1-480705-5
NATURAL	1-480705-6
COLORED	1-480705-7
2-PIN PLATELET	1-480705-8

METRIC

