

M 480709

SCHEDA TECNICA

1. MADE WITH APPROPRIATE UNIVERSAL SWITCH-LOCK PUNCH
 2. RECOMMENDED PANEL THICKNESS 0.75 - 2.29
 3. PANEL MUST BE PUNCHED SO THAT THE HOUSING REIDES THE PANEL IN THE SAME DIRECTION AS THE PUNCH
 △ OPTIMAL FOR KEYS HOUSING IN PANEL
 △ ABOUT NUMBER 1 LOCATION
 △ DIMENSION INDICATED IS AS WELDED. ADDITIONAL WORKS DUE TO SUBSEQUENT ROTURE RESISTION MAY OCCUR
 △ FOUR RIBS EQUALLY SPACED, NO SPECIFIC DIMENSIONING. RIBS OR RIBS EQUALLY SPACED, NO SPECIFIC DIMENSIONING, OPTIONAL
 △ UNDERWRITERS RECOMMENDED COMPONENT LOAD AND CSA CERTIFICATION LOAD TO BE LOCATED ONCE EACH ON ONE OF HOUSING
 △ OBSOLETE PARTS, OBSOLETE CS STREAMING PER OPENING/DIMENSION

CONVERSION TABLE

6.50	275	127	4.3	1.083
4.25	175	72.5	1.083	
6.50	110	48.1	1.083	
2.54	100	38.1	1.050	
6.50	100	38.1	1.050	
0.76	0.50	20.32	0.50	
0.50	0.13	3.18	0.50	
0.25	0.10	2.54	0.50	
0.13	0.05	1.27	0.50	
MM	IN	MM	IN	

METRIC



1. STAMP NUMBERS 0.18 HIGH AT WIRE END OF HOUSING (12 POINT DASH TYPE) CLARIFICATION MARKS UNDER THE 4 & 6
 2. CHARACTERS TO BE STAMPED ON HOUSING IN A MANNER AS TO BE READ FROM WIRE END ONLY
 3. VIOLET, BLACK, BROWN AND BLUE COLORED BLOCKS TO BE STAMPED WITH WHITE CHARACTER. ALL OTHER COLORED BLOCKS TO BE STAMPED WITH BLACK CHARACTER

CONVERSION TABLE

6.50	200	-	-	-
4.50	180	27.43	1.083	
3.18	125	24.67	1.050	
0.38	0.10	25.51	1.050	
0.25	0.10	20.32	0.50	
0.13	0.05	8.13	0.50	
MM	IN	MM	IN	

METRIC

