

# M 776487-3

# SCHEDA TECNICA



REVISIONI

NO.	REVISIONE	DATA	REVISIONE	CAUSA
01	REVISO PER ECO-11-03/14			
02	REVISO PER ECO-13-01/14			

776487-2 SCALE 2:1  
 776487-3 SCALE 2:1  
 776487-4 SCALE 2:1

Ø2,00 REF  
 4 PLC  
 4,50 REF  
 5,30 REF  
 23,33±0,20  
 776487-1 SHOWN  
 26,8 MAX  
 2,25 REF  
 2,65 REF

SECTION B-B

PLUG HOUSING  
 PERIPHERAL SEAL  
 (PRE-STAGED POSITION)  
 PLUG TPA  
 PLUG COVER  
 WIRE SEAL  
 36,70 MIN WITH TPA IN OPEN POSITION  
 SECTION A-A

SCALE 2:1

▲ MATERIAL: 15% GLASS FILLED THERMOPLASTIC  
 COLOR: BLACK  
 ▲ MATERIAL: 15% GLASS FILLED THERMOPLASTIC  
 COLOR: (SEE TABLE)  
 ▲ MATERIAL: SILICONE  
 COLOR: GREEN  
 ▲ MATERIAL: 15% GLASS FILLED THERMOPLASTIC  
 COLOR: RED  
 5. RECOMMENDED WIRE DIAMETER RANGE IS 2,18 TO 3,67mm  
 ▲ MATERIAL: SILICONE  
 COLOR: TAN

THIS DRAWING IS A CONTROLLED DOCUMENT  
 776487-3  
 776487-3  
 776487-2  
 776487-1  
 776487-4  
 776487-3  
 776487-2  
 776487-1

GREEN 776487-4  
 YELLOW 776487-3  
 GRAY 776487-2  
 RED 776487-1

IT CONNECTIVITY  
 PLUG ASSEMBLY,  
 4 POSITION, DUAL ROW,  
 WITH SEAL, 18  
 776487  
 PART NUMBER