

Form	Bezeichnung	für NW Normalprofil A-B-C	für NW AHW A-B-C	b mm	l mm	Art.-Nr.	VE Stck.
Form	Description	for NW normal profile A-B-C	for NW AHW A-B-C	b mm	l mm	Art. no.	PU pcs.
B	mit Steckfuß/with plug socket	17 - 10 - 17	15 - 8,5 - 15	37,0	43,8	9806136	500
B	mit Steckfuß/with plug socket	17 - 13 - 13	15 - 11 - 11	36,9	46,0	9806166	500
B	mit Steckfuß/with plug socket	17 - 13 - 17	15 - 11 - 15	36,3	50,1	9806141	250
B	mit Steckfuß/with plug socket	17 - 17 - 7,5	15 - 15 - 6	36,9	50,6	9806167	500
B		17 - 22 - 17	15 - 19 - 15	39,3	59,9	9806135	250
B		22 - 4,5 - 22	19 - 4,5 - 19	37,7	41,4	9806106	500
B		22 - 7,5 - 22	19 - 6 - 19	41,4	39,5	9806113	500
B		22 - 8,5 - 22		47,0	66,4	9806149	500
B		22 - 10 - 10	19 - 8,5 - 8,5	47,0	66,3	9806143	500
B		22 - 10 - 17	19 - 8,5 - 15	47,0	67,7	9806179	*)
B		22 - 10 - 22	19 - 8,5 - 19	41,5	42,5	9806121	500
B	glatt/smooth	22 - 10 - 22	19 - 8,5 - 19	66,4	47,0	9806164	*) 100
B		22 - 13 - 17	19 - 11 - 15	41,4	46,7	9806114	250
B		22 - 13 - 22	19 - 11 - 19	41,4	46,4	9806108	500
B	mit Steckfuß/with plug socket	22 - 17 - 13	19 - 15 - 11	41,9	51,3	9806103	250
B		22 - 22 - 10				9806178	250
B		22 - 22 - 13	19 - 19 - 11	43,8	58,5	9806142	250
B		22 - 22 - 22	19 - 19 - 19	42,4	56,2	9806102	250
B	glatt/smooth	22 - 22 - 22	19 - 19 - 19	66,4	47,0	9806165	*) 500
B		22 - 26 - 17	19 - 26 - 15	42,5	57,0	9806184	250
B		22 - 29 - 26		48,5	60,0	9806182	250
B		26 - 4,5 - 22	26 - 4,5 - 19	53,0	72,3	9806153	100
B		26 - 4,5 - 26	26 - 4,5 - 26	53,0	73,0	9806144	500
B		26 - 7,5 - 22	26 - 6 - 19	53,0	72,3	9806156	*)
B		26 - 7,5 - 26	26 - 6 - 26	53,0	73,0	9806177	*)
B		26 - 8,5 - 26		53,0	73,0	9806145	500
B		26 - 10 - 26	26 - 8,5 - 26	47,6	45,1	9806129	500
B		26 - 13 - 13	26 - 11 - 11	53,0	72,9	9806140	500
B		26 - 13 - 22	26 - 11 - 19	53,0	72,3	9806148	500
B		26 - 13 - 26	26 - 11 - 26	53,0	73,0	9806147	500
B		26 - 17 - 17	26 - 15 - 15	49,0	52,5	9806109	250
B		26 - 17 - 22	26 - 15 - 19	47,3	50,7	9806119	500
B		26 - 17 - 26	26 - 15 - 26	53,0	73,0	9806146	500
B		26 - 22 - 22	26 - 19 - 19	47,3	55,2	9806112	250
B		26 - 26 - 10	26 - 26 - 8,5	72,2	53,0	9806174	*)
B		26 - 26 - 13	26 - 26 - 11	53,0	72,9	9806134	500
B		26 - 26 - 22	26 - 26 - 19	47,4	61,2	9806110	250
B		26 - 26 - 26	26 - 26 - 26	53,0	73,0	9806157	500
B		29 - 10 - 29		53,5	59,6	9806300	*)
B		29 - 13 - 29		51,5	41,5	9806183	250
B		29 - 17 - 26		51,4	46,4	9806181	250
B		29 - 17 - 29		53,5	59,6	9806301	500
mit Bügelverschluss /with clamp-lock							
mit Außeneinhängekontur an Abgang C /with exterior hook-up profile to connection C							
mit Innenanschlag zur Begrenzung des Wellschlauchs /with interior stop ridge to limit the corrugated tube							
C	mit Steckfuß/with plug socket	7,5 - 4,5 - 4,5	6 - 4,5 - 4,5	24,7	37,7	9806125	1000
C		10 - 8,5 - 8,5		29,1	36,0	9806188	500
C		10 - 8,5 - 10		29,1	42,2	9806189	500
C		10 - 10 - 8,5		29,1	37,0	9806185	500
C		10 - 13 - 10	8,5 - 11 - 8,5	29,1	46,2	9806186	500
C	mit Steckfuß/with plug socket	13 - 4,5 - 10	11 - 4,5 - 8,5	30,6	39,5	9806127	500
C	mit Steckfuß/with plug socket	13 - 8,5 - 13		31,6	42,4	9806118	1400
C	mit Steckfuß/with plug socket	13 - 13 - 13	11 - 11 - 11	31,9	46,6	9806115	500
C	mit Steckfuß/with plug socket	17 - 8,5 - 17		36,9	46,0	9806120	250
C		17 - 17 - 13	15 - 15 - 11	37,2	51,9	9806187	500
C		22 - 22 - 17	19 - 19 - 15	43,8	60,6	9806126	900
C		22 - 23 - 10		42,2	60,6	9806116	250
C		22 - 23 - 13		42,2	61,3	9806117	250
C		23 - 22 - 22		46,6	58,4	9806122	250
C		26 - 17 - 10	26 - 15 - 8,5	49,0	51,8	9806123	250
C		26 - 17 - 13	26 - 15 - 11	49,0	52,2	9806124	250
C		26 - 22 - 23		49,7	57,6	9806128	250
mit Bügelverschluss /with clamp-lock							
mit Außeneinhängekontur an Abgang A /with exterior hook-up profile to connection A							
D		10 - 7,5 - 7,5	8,5 - 6 - 6	28,7	39,7	9806130	2000
D	mit Steckfuß/with plug socket	13 - 10 - 10	11 - 8,5 - 8,5	31,9	43,6	9806131	500

