

M DRC16-70SA-P013

SCHEMA TECNICA



REV		DESCRIPTION		DATE		APPROVED	
A	DRCB-70SA-P013	NEW RELEASE PER E.O. P15136		01-15-96		808	
		REVISED PER E.O. P17133				AWC	

MIN. INSUL. O. D.	MAX. INSUL. O. D.	WIRE RANGE (mm ²) REF ENCL. A
12.180	12.134	14-28 AWG
12.543	12.481	12-6-0-5B1

4.094 (103.993)

1.421 (36.943)

1.543 (39.173)

.158 (3.981)

.057 (1.451)

.109 (2.741)

8. MATING TORQUE REQUIREMENT: 25-28 IN-LB (2.82-3.13 Nm).

7. SEE SHEET 2 FOR OTHER KEY ARRANGEMENTS.

6. MATERIAL - PLUG: PLASTIC; SEAL/O-RING: RUBBER; RETAINING BOLT: STEEL.

5. THIS PLUG MATES WITH ENCL-170P-***, DRC13-70P-*** AND DRC14-70P-*** RECEIPTABLE (A, B, C, D KEYS: ***-ALL MODIFICATIONS). CONSULT FACTORY FOR MOQS.

4. FOR CONTACTS AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS, SEE ENVELOPE DRAWING 6425-015-880.

3. PLUG SUPPLIED WITH ORST CAP. (NOT SHOWN).

2. DIMENSION TOLERANCE: ±.025 (.641).

1. DIMENSIONS ARE IN INCHES (mm).

NOTES: UNLESS OTHERWISE SPECIFIED

▲ PART MODIFICATION: INTERFACE SEALS ARE BOMDED TO PLUG HOUSING.

REV	DESCRIPTION & DATE	BY	CHKD	DATE
01	70 SIZE 16 PLUG			
02	KEYS: A, B, C, D			
03	COLOR: BLACK			
04	DRC SERIES			

The Deutsch Company DIVISION OF DEUTSCH ELECTRIC AND TELEPHONE CORP. 1000 WEST 15TH AVENUE DENVER, COLORADO 80202	DRCB-70SA-P013 SHEET 1 OF 2
---	---------------------------------------