

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	NEW RELEASE PER PCN E-21-003453	22NOV2021	MM	IG




FIGURE 1




FIGURE 3
LONG CAP

4 "E" IDENTIFIES E-SEAL, LOCATED APPROX. AS SHOWN.

3 MATERIAL: HOUSING: PA66 GF15, SEE TABLE FOR COLOR
SHORT, LONG CAP: PA66 GF15, SEE TABLE FOR COLOR
GROMMET: E-SEAL VMO (BURNT RED)
N-SEAL VMO (RED-ORANGE)
BLOCKED VMO (RED-ORANGE)
FRONT SEAL: VMO (RED-ORANGE),

2. THIS PLUG MATES WITH DT04-12PX-XXXX RECEPTACLE.
(XXXX = ALL MODIFICATION)

1. SECONDARY WEDGE LOCK SOLD SEPARATELY: W12S-XXXX.
(XXXX = ALL MODIFICATIONS)
W12S OR W12S-P012 MAY BE USED WITH THESE PLUGS,
W12S-P012 IS RECOMMENDED.

NOTE: UNLESS OTHERWISE SPECIFIED

6 MARKING FOR PARTS PRODUCED IN CHINA:

-XXXX IDENTIFIES THE MODIFICATION NUMBER,
IF APPLICABLE. EXAMPLE: *E003 FOR DT06-12SX-E003,
OR BLANK FOR DT06-12SX

-DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY.
YEAR: FIRST AND SECOND DIGITS. (17 = 2017)
MONTH: THIRD DIGIT , EXCLUDING I. A = JAN, B = FEB,
C = MARCH... (K = OCTOBER)
DAY: FOURTH AND FIFTH DIGITS (14 =14th DAY)
HOUR: SIXTH AND SEVENTH DIGITS (11 = 11AM)

-DIAL DATE CODE LOCATED ON HOUSING AND/OR CAP.
-CN LOCATED ON HOUSING AND/OR CAP.

5. FOR CONTACTS AND WIRE PERFORMANCE AND APPLICATION
CHARACTERISTICS SEE CUSTOMER DRAWING 0425-015-0000.

7 MARKING FOR PARTS PRODUCED IN US:
-DATE CODE:
YEAR TO BE LAST NUMERICAL DIGIT,
EX: 1=2021
MONTH USES SEQUENTIAL ALPHA CHARACTERS,
EX: A=JANUARY







FIGURE 2
SHORT CAP

ALT.VIEW FOR
PARTS FROM CHINA

TE INTERNAL PART NUMBER	DEUTSCH PART NUMBER	PN REV	COLOR	STANDARD SEAL	EXTRA THIN SEAL E SEAL	BLOCKED SEAL	ENHANCED KEY	SHORT CAP	LONG CAP	FIGURE
DT06-12SX	DT06-12SX	A	ALL	X						1
DT06-12SX-B016	DT06-12SX-B016	A	ALL	X			X			1
DT06-12SX-BE01	DT06-12SX-BE01	A	ALL	X			X	X		2
DT06-12SX-C015	DT06-12SX-C015	B	ALL		X					1
DT06-12SX-C017	DT06-12SX-C017	A	ALL			X		X		2
DT06-12SX-CE01	DT06-12SX-CE01	C	ALL		X			X		2
DT06-12SA-CE02	DT06-12SA-CE02	B	BLACK		X					1
DT06-12SA-CE03	DT06-12SA-CE03	A	BLACK		X			X		2
DT06-12SX-CE04	DT06-12SX-CE04	B	ALL		X				X	3
DT06-12SX-CE05	DT06-12SX-CE05	B	ALL		X		X	X		2
DT06-12SX-CE06	DT06-12SX-CE06	B	ALL		X		X			1
DT06-12SA-CE10	DT06-12SA-CE10	B	BLACK		X		X			1
DT06-12SA-CE11	DT06-12SA-CE11	B	BLACK		X		X	X		2
DT06-12SA-CE12	DT06-12SA-CE12	B	BLACK		X		X		X	3
DT06-12SX-CE13	DT06-12SX-CE13	B	ALL		X		X		X	3
DT06-12SX-E003	DT06-12SX-E003	B	ALL	X				X		2
DT06-12SA-E005	DT06-12SA-E005	A	BLACK	X						1
DT06-12SX-E008	DT06-12SX-E008	B	ALL	X					X	3
DT06-12SX-EP04	DT06-12SX-EP04	C	ALL	X				X		2
DT06-12SX-EP06	DT06-12SX-EP06	C	ALL	X			X	X		2
DT06-12SA-EP07	DT06-12SA-EP07	A	BLACK	X			X			1
DT06-12SA-EP08	DT06-12SA-EP08	B	BLACK	X			X	X		2
DT06-12SA-EP11	DT06-12SA-EP11	A	BLACK	X			X		X	3
DT06-12SX-EP20	DT06-12SX-EP20	A	ALL	X			X		X	3
DT06-12SX-P004	DT06-12SX-P004	B	ALL	X						1
DT06-12SX-P012	DT06-12SX-P012	B	ALL	X			X			1

CONTACT SIZE		WIRE RANGE		INSULATION OD SEALING RANGE		SEAL IDENTIFICATION		THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN R. MUKESH 22NOV2021		 TE Connectivity							
16		14-20 AWG [2.5-0.5 mm ²]		.088-.145 [2.23-3.68] .053-.120 [1.35-3.05]		STANDARD SEAL EXTRA THIN SEAL E-SEAL		DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK R. MESSENGER 22NOV2021									
								1 IN[mm]		0 PLC ± 2 PLC ± 3 PLC ± 4 PLC ±		02510-.64) ± ± ±		APVD I. GRANTCHAROVA 22NOV2021		NAME 12 WAY PLUG, STANDARD SEAL EXTRA THIN SEAL, SHORT AND LONG CAP DT SERIES					
												PRODUCT SPEC 108-151009		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO	
												APPLICATION SPEC 114-151009		A		4AUF8		C=DT06-12SX-XXXX		-	
												ANGLES ±0°30'0"									
												FINISH									
												MATERIAL									
																					

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-



AFFECTED PART NUMBERS	PN REV	COLOR	STANDARD SEAL	EXTRA THIN SEAL E-SEAL	BLOCKED SEAL	SHORT CAP	LONG CAP	FIGURE
DT06-12SX	-	ALL	X					1
DT06-12SX-C015	A	ALL		X				1
DT06-12SX-C017	-	ALL			X	X		2
DT06-12SX-CE01	B	ALL		X		X		2
DT06-12SA-CE02	A	BLACK		X				1
DT06-12SA-CE03	-	BLACK		X		X		2
DT06-12SX-CE04	A	ALL		X			X	3
DT06-12SX-E003	A	ALL	X			X		2
DT06-12SA-E005	-	BLACK	X					1
DT06-12SX-E008	A	ALL	X				X	3
DT06-12SX-EP04	B	ALL	X			X		2
DT06-12SX-P004	A	ALL	X					1

9. SECONDARY WEDGE LOCK SOLD SEPARATELY: W12S
W12S MUST BE USED WITH THE STANDARD TYPE PLUGS.

THE AFFECTED PARTS NUMBERS LISTED ARE CHANGING FROM STANDARD TYPE SEAL (SHEET 2) TO RETENTION TYPE SEAL (SHEET 1).
PARTS WILL BE SUPPLIED FROM THE NORTH AMERICA REGION IN THE STANDARD TYPE CONFIGURATION UNTIL THE STANDARD TYPE TOOLING REACHES ITS END OF LIFE,
PARTS PRODUCED IN CHINA WILL BE RETENTION TYPE ONLY.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
1 [mm]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±
1 PLC ±
2 PLC ±
3 PLC ±.025[0.64]
4 PLC ±
ANGLES ±0°30'0"

MATERIAL

FINISH

DWN R. MUKESH 22NOV2021
CHK R. MESSENGER 22NOV2021
APVD J. GRANTCHAROVA 25NOV2021

PRODUCT SPEC
108-151009
APPLICATION SPEC
114-151009
WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME 12 WAY PLUG, STANDARD SEAL
EXTRA THIN SEAL, SHORT AND LONG CAP
DT SERIES


SIZE A | 4AFU8 | C=DT06-12SX-XXXX

RESTRICTED TO -


SCALE 2:1 | SHEET 2 OF 3 | REV A

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-


DT06-12SA-XXXX
KEY ARR. -A-
COLOR: GRAY
SEE PN TABLE FOR BLACK PNs.




DT06-12SB-XXXX
KEY ARR. -B-
COLOR: BLACK



DT06-12SC-XXXX
KEY ARR. -C-
COLOR: GREEN



DT06-12SD-XXXX
KEY ARR. -D-
COLOR: BROWN



THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
IN[mm]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC
1 PLC
2 PLC
3 PLC
4 PLC
ANGLES
FINISH

±"
±"
±"
±"
±"
±0°30'0"

MATERIAL

DWN
R. MUKESH
22NOV2021

CHK
R. MESSENGER
22NOV2021

APVD
J. GRANTCHAROVA
25NOV2021

PRODUCT SPEC
108-151009

APPLICATION SPEC
114-151009

WEIGHT
-

CUSTOMER DRAWING

NAME
12 WAY PLUG, STANDARD SEAL
EXTRA THIN SEAL, SHORT AND LONG CAP
DT SERIES

SIZE
A

CAGE CODE
4AFU8

DRAWING NO
DT06-12SX-XXXX

RESTRICTED TO
-

SCALE
5:1

SHEET
3

OF
3

REV
A