M DT06-02S

SCHEDA TECNICA

CONTACT SIZE	WIRE RANGE	INSULATION OD SEALING RANGE	SEAL IDENTIFICATION
16	14-20 AWG (2.5-0.5mm²)	.080-.145 (2.03-3.68)	STANDARD SEAL
		.135-.145 (3.43-3.68)	EXTRA THIN WALL SEAL
			LARGE SEAL

TE INTERNAL PART NUMBER	DEUTSCH PART NUMBER	PIN QTY	COLOR	STANDARD SEAL & GROMMET	EXTRA THIN WALL SEAL & GROMMET	SHORT CAP	LONG CAP	FIGURE
DT06-2S	DT06-2S	2	GREY	X				1
DT06-2S-C015	DT06-2S-C015	2	GREY		X	X		1
DT06-2S-C001	DT06-2S-C001	2	GREY		X	X		2
DT06-2S-C003	DT06-2S-C003	2	BLACK		X	X		2
DT06-2S-C004	DT06-2S-C004	2	GREY		X	X	X	3
DT06-2S-C005	DT06-2S-C005	2	BLACK		X	X	X	3
DT06-2S-C006	DT06-2S-C006	2	BLACK		X	X	X	3
DT06-2S-C013	DT06-2S-C013	2	BLACK		X	X	X	3
DT06-2S-C003	DT06-2S-C003	2	GREY	X			X	2
DT06-2S-C004	DT06-2S-C004	2	BLACK	X			X	2
DT06-2S-C005	DT06-2S-C005	2	BLACK	X		X	X	2
DT06-2S-C008	DT06-2S-C008	2	GREY	X		X	X	2
DT06-2S-CP04	DT06-2S-CP04	2	GREY	X		X	X	2
DT06-2S-CP06	DT06-2S-CP06	2	BLACK	X		X	X	2
DT06-2S-CP11	DT06-2S-CP11	2	BLACK	X		X	X	2
DT06-2S-P004	DT06-2S-P004	2	BLACK	X		X	X	2
DT06-2S-P012	DT06-2S-P012	2	BLACK	X		X	X	2

mes connettori

componenti per il cablaggio