

M DTM12S-BT

SCHEDA TECNICA

2019

RELEASED FOR PUBLICATION

THIS DRAWING IS UNPUBLISHED.

© COPYRIGHT 2014

TE Connectivity. All rights reserved.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DMN	APVD	
A		NEW RELEASE PER ECO-14-010245		05AUG2014	DM	DM	
A1		REVISED PER PCN E-18-002290		15FEB2018	DD	DM	
A2		REVISED PER PCN E-19-014637		02OCT2019	JA	IG	

SCALE 3:4

MEASURED 6.35±0.64 [0.250±.025] FROM OPEN END

69.93±3.81 [2.753±.150]

Ø 10.92 [0.430]

(29.46) [1.160]

(37.24) [1.466]

(11.71) [0.461]

(14.94) [0.588]

1.52±0.25 [0.060±.010]

4

4 SMALL MATERIAL EXTENSION IS ACCEPTABLE ON THIS END ALL AROUND.

3. THIS ACCESSORY PART IS PROVIDED WITHOUT TYPICAL TRANSPORTATION INDUSTRY PROCESS CONTROL. NO VALIDATION TESTING HAS BEEN PERFORMED. CUSTOMER IS RESPONSIBLE FOR DETERMINING PRODUCT PERFORMANCE AND SUITABILITY FOR APPLICATION.

2. TEMPERATURE RATING: -29°C TO +100°C [-20°F TO +212°F]

1. THIS PART IS USED ON DTM06-12SX (X=A,B,C,D KEYS) PLUG WITH ANY MODIFICATION THAT DOES NOT INCLUDE AN END CAP.

TE INTERNAL PN		DEUTSCH PN	
DTM12S-BT		DTM12S-BT	

DIMENSIONS:		DMN	07JUL2014	MATERIAL	PVC	FINISH	GRAY
mm [INCHES]		CHK	07JUL2014	 TE Connectivity			
TOLERANCES UNLESS OTHERWISE SPECIFIED		B. MILLIGAN					
		APVD					
0 PLC ±		D. MEYER					
1 PLC ±		PRODUCT SPEC		NAME			
2 PLC ±		APPLICATION SPEC		BOOT, PLUG, 12PIN			
3 PLC ±0.63 [0.025]				DTM SERIES			
4 PLC ±				SIZE		DRAWING NO	
ANGLES ±0° 30' 0"				A 4		CAGE CODE	
				4AFU8		DRAWING NO	
				C=DTM12S-BT		RESTRICTED TO	
				WEIGHT		-	
				6.52g			
				CUSTOMER DRAWING			
				SCALE		SHEET	
				5:4		1 OF 1	
						REV	
						A2	

