

M DTM3S-BT

SCHEDA TECNICA

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
A		NEW RELEASE PER ECO-14-010241		07JUL2014	DM	DM	
A1		REVISED PER PCN-E-19-015669		08OCT2019	JA	IG	

SCALE 1:1

Dimensions (mm [INCHES]):

- (12.70) [.500]
- (6.99) [.275]
- (10.16) [.400]
- (15.88) [.625]
- 63.50±3.81 [2.500±.150]
- 1.52±0.25 [.060±.010]
- MEASURED 6.35±0.64 [.250±.025]
- FROM OPEN END
- Ø6.35 [.250]

4

RELEASED FOR PUBLICATION 2019

THIS DRAWING IS UNPUBLISHED. © COPYRIGHT 2014 TE Connectivity. All Rights Reserved.

1. THIS PART IS USED ON DTM06-3S PLUGS WITH ANY MODIFICATION THAT DOES NOT INCLUDE AN END CAP.

2. TEMPERATURE RATING: -29°C TO +100°C [-20°F TO +212°F].

3. THIS ACCESSORY PART IS PROVIDED WITHOUT TYPICAL TRANSPORTATION INDUSTRY PROCESS CONTROLS. NO VALIDATION TESTING HAS BEEN PERFORMED. CUSTOMER IS RESPONSIBLE FOR DETERMINING PRODUCT PERFORMANCE AND SUITABILITY FOR APPLICATION.

4. SMALL MATERIAL EXTENSION IS ACCEPTABLE ON THIS END ALL AROUND.

TE INTERNAL PN		DEUTSCH PN	
DTM3S-BT		DTM3S-BT	

DIMENSIONS:		DWN	07JUL2014	MATERIAL	PVC	FINISH	GRAY
mm [INCHES]		D. MEYER					
TOLERANCES UNLESS OTHERWISE SPECIFIED		CHK	07JUL2014				
		B. MILLIGAN					
		APVD	07JUL2014				
0 PLC ±		PRODUCT SPEC		NAME		BOOT, PLUG, 3PIN	
1 PLC ±		APPLICATION SPEC		SIZE		DTM SERIES	
2 PLC ±		WEIGHT		CAGE CODE		DRAWING NO	
3 PLC ±0.64 [.025]				A 4		4AFU8	
4 PLC ±		CUSTOMER DRAWING		RESTRICTED TO		-	
ANGLES ±0° 30' 0"		SCALE		SHEET		1 OF 1	
						REV A1	

