

For electrovalves, style A, 2p+G or 3p+G, female, field attachable
Per elettrovalvole, stile A, 2p+T o 3p+T, femmina, da cablare

EN175301-803 style A square connector,
(former DIN 43650-A), ISO 4400:
built-in gasket;
central screw total insulation;
SMD components to let more assembling space;
crimp terminals option;
application with electrovalves, etc.

connettore quadrato EN175301-803 stile A,
(ex DIN 43650-A), ISO 4400:
guarnizione integrata;
vite centrale totalmente isolata;
componenti SMD per lasciare più spazio per il montaggio;
disponibile con terminali liston;
applicazione con elettrovalvole, ecc.



General characteristics
housing material: PA66 30%GF
contact material: nickel plated CuZn
max wires section: 1.50 mm²
protection degree IEC 60529: IP67
working temperature: -40...125° C (max 70° C with electronic components)
oil resistance: good
M3 central screw material: zinc plated iron (for stainless steel, see table E)

Caratteristiche generali
materiale rivestimento: PA66 30%GF
materiale contatti: CuZn nichelato
max sezione fili: 1.50 mm²
grado protezione IEC 60529: IP67
temperatura di lavoro: -40...125° C (max 70° C con componenti elettronici)
resistenza olio: buona
materiale vite centrale M3: ferro zincato (per acciaio inox, vedere tabella E)

circuit schema circuit (a2)	description descrizione	voltage tensione Vdc	voltage tensione Vac	max current corrente max A	clamping voltage tensione intervento V	housing colour colore rivestimento	ipo contatto contact type
--------------------------------------	----------------------------	----------------------------	----------------------------	--	--	---	------------------------------

M EV1388

1 → BN 2 → BU 3 → Y/G	without electronic senza elettronica	1.250	1.250	10	—	black nero	
-----------------------------	---	-------	-------	----	---	---------------	--

M EV1395

1 → BN 2 → BU 3 → Y/G	red Led Led rosso (a7)	10.50	10.50	10	—	transp. trasp.	
-----------------------------	------------------------------	-------	-------	----	---	-------------------	--

M EV1392

1 → BN + 2 → BU 3 → Y/G	red Led + diode Led rosso + diodo (a7)	10.50	—	10	V+1	transp. trasp.	
-------------------------------	--	-------	---	----	-----	-------------------	--

3-point
contact
contatto a
3 punti

