



RECOMMENDED MOUNTING HOLE

RECOMMENDED MOUNTING HOLE

RECOMMENDED MOUNTING HOLE

REV	DESCRIPTION	DATE	APPROVED
1	NEW RELEASE PER E.O. P16409	2-4-06	MB
2	REVISION PER E.O. P16875	9/29/06	MB
3	REVISION PER E.O. P17391	12/11/06	MB
4	REVISION PER E.O. P16449	2-14-08	MB

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
1	NEW RELEASE PER E.O. P16409	2-4-06	MB
2	REVISION PER E.O. P16875	9/29/06	MB
3	REVISION PER E.O. P17391	12/11/06	MB
4	REVISION PER E.O. P16449	2-14-08	MB

NOTES:

- THIS PART MATES WITH HDP24-18-4S1P-XXXX (XXXX = ALL MODIFICATIONS, # = TYPE OF STEEL.)
- FOR ARRANGEMENT OF CONTACT LOCATION SEE ENVELOPE DRAWING 8423-013-1000.
- FOR CONTACTS, WIRES, CONNECTOR PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 8423-815-0009 AND 0423-021-9898.
- DIMENSIONS ARE IN INCHES (MILLIMETERS).
- RECOMMENDED PANEL THICKNESS: .0625 (1.588) TO .1875 (4.763).
- THIS RECEPTACLE TO BE USED WITH 114928-98 (ALUMINUM) OR 2411-002-1895 (PLASTIC) PANEL MNT AND 2414-002-1895 LOCK WASHER.

1. DIMENSION TOLERANCES ARE ±.025 (±.635) UNLESS OTHERWISE NOTED.

REV	DESCRIPTION	DATE	APPROVED
1	NEW RELEASE PER E.O. P16409	2-4-06	MB
2	REVISION PER E.O. P16875	9/29/06	MB
3	REVISION PER E.O. P17391	12/11/06	MB
4	REVISION PER E.O. P16449	2-14-08	MB

REV	DESCRIPTION	DATE	APPROVED
1	NEW RELEASE PER E.O. P16409	2-4-06	MB
2	REVISION PER E.O. P16875	9/29/06	MB
3	REVISION PER E.O. P17391	12/11/06	MB
4	REVISION PER E.O. P16449	2-14-08	MB

REV	DESCRIPTION	DATE	APPROVED
1	NEW RELEASE PER E.O. P16409	2-4-06	MB
2	REVISION PER E.O. P16875	9/29/06	MB
3	REVISION PER E.O. P17391	12/11/06	MB
4	REVISION PER E.O. P16449	2-14-08	MB