



REV	DESCRIPTION	DATE	APPROVES
C	HDP24-18-21S		
MC	REV RELEASE PER E.O. P16600	2-4-16	BBB
A	REVISE PER E.O. P16875	9/29/09	BBB
B	REVISED PER E.O. P17591	1/17/02	BBB
C	REVISED PER E.O. P18449	2-24-04	BBB

  

RECOMMENDED MOUNTING HOLE

1.598 - 18 INCH REF. THROUGH

NOTES:

- THIS PART MATES WITH HDP26-18-431P-\*\*\*\*\* (\*\*\*\*\* = ALL MODIFICATIONS, \* = TYPE OF SEAL.)
- FOR ARRANGEMENT OF CONTACT LOCATION SEE ENVELOPE DRAWING 8425-013-1000.
- FOR CONTACTS, WIRES, CONNECTOR PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 8425-415-0000 AND 8425-021-9988.
- DIMENSIONS ARE IN INCHES (MILLIMETERS).
- RECOMMENDED PANEL THICKNESS: .06211, .581 TO .18714, .783.
- THIS RECEPTACLE TO BE USED WITH 114828-18 (ALUMINUM) OR 2411-002-1885 (PLASTIC) PANEL MOUNT AND 2414-002-1895 LOCK WASHER.

1. DIMENSION TOLERANCES ARE ±.025 (±.63) UNLESS OTHERWISE NOTED.

<p>RECEPTACLE CONNECTOR</p> <p>SHELL SIZE 18</p> <p>BAYONET COUPLING</p> <p>HDP20 SERIES</p> <p>ENVELOPE</p>	<p>RECEIVED</p> <p>The Danish Company</p> <p>50000</p> <p>50000 INDUSTRIAL AV.</p> <p>WELLS, CALIF. 92326</p> <p>DATE: 1/17/02</p> <p>BY: BB</p> <p>SCALE: 1:1</p>
--	--