



NOTE:

- RECEPTACLE IS SUPPLIED WITH DUST CAP (2415-001-2405).
- NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.
- MATERIAL:** RECEPTACLE HOUSING: PA66 GF10 (BLACK)
RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
GROMMET: SILICONE (ORANGE-RED)
- SEE 0425-021-0000 APPLICATION SPECIFICATION
- RECOMMENDED MOUNTING TOOLS
- RECOMMENDED MOUNTING HOLE & PANEL THICKNESS
- MOUNTING HARDWARE & MOUNTING TORQUE.

THIS RECEPTACLE MATES WITH HDP26-24-XXP/SX-XXXX PLUG
 X = SEAL TYPE (N, I, E)
 XX = INSERT ARRANGEMENT
 XXXX = MODIFICATION

SEE CUSTOMER DRAWING, 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

NOTES:

DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY
 YEAR: FIRST AND SECOND DIGITS (1A = 201A)
 MONTH: THIRD DIGIT - EXCLUDING 1, A = JAN, B = FEB, C = MARCH, N = OCTOBER
 DAY: FOURTH AND FIFTH DIGITS (1A = 14TH DAY)
 HOUR: SIXTH AND SEVENTH DIGITS (11 = 11AM)

SCALE 1:1

Labels in drawing: FLAT, MAIN POLARIZING KEYWAY, RETAINING RING, RECEPTACLE HOUSING, DUST CAP, POLARIZING INDICATOR, CONTACT INSERTION THIS SIDE, GROMMET, DATE CODE, RETAINER RING, HOUSING, POLARIZING INDICATOR.

Dimensions: $\varnothing 2,000$ (150,801), 1,875 (147,631), (1,618) (141,101), (1,030) (126,161), 1,648±.025 (141,86±0,631), 1,100 (12,541), $\varnothing 1,470\pm.020$ (137,34±0,511), 1,171X1.

REVISIONS

REV	DATE	BY	CHK	DESCRIPTION
1				REVISED PER E.O P21391
2				REVISED PER ECO-14-019072
3				REVISED PER PCH E-16-012886
4				REVISED PER PCH E-18-013271

Customer Drawing

STE TE Connectivity

RECEPTACLE, THREADED
 SIZE 24
 HDP SERIES

0425-021-0000

44F08 HDP24-24-XXP/SX