



MECCANISMO DI CONNETTIVITÀ MICROBIPOLARE A 24 PINI

REVISIONS

REV.	DATE	DESCRIPTION	BY	CHK
H	15/09/12	REVISED PER E.O. P21391	AM	BM
J	27/09/15	REVISED PER ECO-14-019072	JA	DM
J1	09/09/16	REVISED PER FCN E-16-012306	DM	DM
J2	06/07/18	REVISED PER FCN E-18-015127	JA	DM

NOTE:

- RECEPTACLE IS SUPPLIED WITH DUST CAP (2413-001-24051).
- NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.
- MATERIAL: RECEPTACLE HOUSING: PA66 GF10 (BLACK)
RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
GROMMET: SILICONE (ORANGE-RED)
- SEE 0425-021-0000 APPLICATION SPECIFICATION
A. RECOMMENDED WIRE INSULATION RANGE
B. CONTACT REMOVAL TOOLS
C. RECOMMENDED MOUNTING HOLE & PANEL THICKNESS
D. MOUNTING HARDWARE & MOUNTING TORQUE.
- THIS RECEPTACLE MATES WITH HDP26-24-XXP/SX-XXXX PLUG
X = SEAL TYPE (N, T, E)
XX = INSERT ARRANGEMENT
XXXX = MODIFICATION

DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY
YEAR: FIRST AND SECOND DIGITS (14 = 2014)
MONTH: THIRD DIGIT (EXCLUDING 1, A = JAN., B = FEB., C = MARCH, D = APRIL, E = MAY, F = JUNE, G = JULY, H = AUGUST, I = SEPTEMBER, J = OCTOBER, K = NOVEMBER, L = DECEMBER)
DAY: FOURTH AND FIFTH DIGITS (14 = 14th DAY)
HOUR: SIXTH AND SEVENTH DIGITS (11 = 11AM)

THIS DRAWING IS A CONTROLLED DOCUMENT.

RECEPTACLE, THREADED
SIZE 24
HDP SERIES

SCALE 1:1

Labels in drawing: FLAT, Ø2,000 (59,801), MAIN POLARIZING KEYWAY, 1,875 (47,631), (1,618) (41,101), (1,030) (26,161), 100 (2,541), 1,648±,025 (41,86±0,631), RECEPTACLE HOUSING, RETAINING RING, GROMMET, POLARIZING INDICATOR, CONTACT INSERTION THIS SIDE, DEUTSCH, HDP24-24-XXP/SX, DATE CODE, DUST CAP, POLARIZING INDICATOR.

Customer Drawing