



REVISIONI

REV.	DATA	DESCRIZIONE	PRODOTTORE	PRODOTTORE
H	15/09/12	REVISIÃO PER E.O.P21391	AM	RSB
J	27/02/15	REVISIÃO PER ECO-14-019972	JM	DM
J1	06/09/17	REVISIÃO PER PCN E-18-012308	DS	DM
J2	06/02/18	REVISIÃO PER PCN E-18-015127	JM	DM

NOTE:

- RECEPTACLE IS SUPPLIED WITH DUST CAP (2415-001-2405).
- NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.
- MATERIAL: RECEPTACLE HOUSING: PA66 GF10 (BLACK) RETAINING RING: PA66 GF10 (GREEN, GRAY, BLUE) GROMMET: SILICONE (ORANGE-RED)
- SEE 0425-021-0000 APPLICATION SPECIFICATION
 - RECOMMENDED WIRE INSULATION SPECIFICATION
 - CONTACT REMOVAL TOOLS
 - RECOMMENDED MOUNTING HOLE & PANEL THICKNESS
 - MOUNTING HARDWARE & MOUNTING TORQUE.
- THIS RECEPTACLE MATES WITH HDP26-24-XXP/SX-XXXX PLUG
 - SEAL TYPE (N, I, E)
 - INSERT ARRANGEMENT
 - MODIFICATION

SEE CUSTOMER DRAWING, 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

THIS DRAWING IS A CONTROLLED DOCUMENT:

REV. 1	DATE 01/11/16	BY 241	CHK 241
REV. 2	DATE 02/02/18	BY 241	CHK 241

Customer Drawing

RECEPTACLE, THREADED
SIZE 24
HDP SERIES

SCALE 1:1

Labels in drawing: FLAT, Ø2,000 (±0,001), MAIN POLARIZING KEYWAY, GROMMET, RETAINING RING, RECEPTACLE HOUSING, DUST CAP, POLARIZING INDICATOR, CONTACT - INSERTION - THIS SIDE, DEUTSCH, HDP24-24-XXP/SX, DATE CODE Z, POLARIZING INDICATOR.