



NOTE: THIS DRAWING IS A CONTROLLED DOCUMENT. ALL RIGHTS RESERVED. 2015

REVISIONS

REV.	DESCRIPTION	DATE	BY	CHK.
H	REVISED PER E.O P21391	14/09/12	AM	BM
J	REVISED PER ECO-14-019972	29/09/14	JM	DM
J1	REVISED PER FCN E-16-012398	09/08/17	DM	DM
J2	REVISED PER FCN E-18-015127	08/03/19	JM	DM

6. RECEPACLE IS SUPPLIED WITH DUST CAP (2415-001-24051).

5. NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

4. MATERIAL: RECEPACLE HOUSING: P666 GF10 (BLACK) RETAINER RING: P666 GF10 (GREEN, GRAY, BLUE) GROMMET: SILICONE (ORANGE-RED)

3. SEE 0425-021-0000 APPLICATION SPECIFICATION
 A. RECOMMENDED WIRE INSULATION RANGE
 B. CONTACT REMOVAL TOOLS
 C. RECOMMENDED MOUNTING HOLE & PANEL THICKNESS
 D. MOUNTING HARDWARE & MOUNTING TORQUE.

2. THIS RECEPACLE MATES WITH HDP26-24-XXP/5X-XXXX PLUG
 X = SEAL TYPE (N, I, E)
 XX = INSERT ARRANGEMENT
 XXXX = MODIFICATION

1. SEE CUSTOMER DRAWING, 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

NOTES:

DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY.
 YEAR: FIRST AND SECOND DIGITS. (14 = 2014)
 MONTH: THIRD DIGIT, EXCLUDING 1, A = JAN., B = FEB., C = MARCH, ... (X = OCTOBER)
 DAY: FOURTH AND FIFTH DIGITS (14 = 14th DAY)
 HOUR: SIXTH AND SEVENTH DIGITS (11 = 11AM)

SCALE 1:1

FRONT VIEW: Dimensions include outer diameter $\varnothing 2,000$ [150,801], main polarizing keyway, and inner diameter $\varnothing 1,476,020$ [37,34E0,511].

SIDE VIEW: Dimensions include total length $1,648,025$ [41,96E0,631], retaining ring length $1,030$ [26,161], and receptacle housing length 100 [2,541].

DETAILS: GROMMET, CONTACT INSERTION THIS SIDE, POLARIZING INDICATOR, DATE CODE, DUST CAP, POLARIZING INDICATOR.

Customer Drawing

STEEL HEADLINE 304/304L
STEEL BODY 304/304L
DATE 0425-021-0000
SIZE HDP SERIES
SCALE 2:1