



THIS DRAWING IS A CONTROLLED DOCUMENT -

REVISIONS

REV	DATE	DESCRIPTION	BY	CHK
1		NEW RELEASE PER E.O. P16512		
2		REVISED PER E.O. P16815		
3		REVISED PER E.O. P18019		
4		REVISED PER ECO-14-019972		

DATE CODE

11/17/19/1

HDP26-24-XXP/SX

CONTACT INSERTION THIS SIDE

DEUTSCH

GROMMET

POLARIZING INDICATOR

MAIN POLARIZING KEY

COUPLING RING

PLUG HOUSING

RETAINING RING

Ø 1,950
149,531
OVER KNURL

1,501±,025
138,63±0,631

Ø 1,410
137,341

Ø 1,950
149,531
OVER KNURL

Ø 1,410
137,341

SCALE 1:1

NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)
RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
GROMMET: SILICONE (ORANGE-RED)

SEE 0425-021-0000 APPLICATION SPECIFICATION
A. RECOMMENDED WIRE INSULATION RANGE
B. CONTACT REMOVAL TOOLS

THIS PLUG MATES WITH HDP24-24XXP/SX-XXXX RECEPTACLE
X = SEAL TYPE (N, J, E)
XX = INSERT ARRANGEMENT
XXXX = MODIFICATION

SEE CUSTOMER DRAWING 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

NOTES:

1. THIS DRAWING IS A CONTROLLED DOCUMENT -

2. THIS PLUG MATES WITH HDP24-24XXP/SX-XXXX RECEPTACLE
X = SEAL TYPE (N, J, E)
XX = INSERT ARRANGEMENT
XXXX = MODIFICATION

3. SEE CUSTOMER DRAWING 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

Customer Drawing

Scale 2:1