

# M HDP26-24-23P\_

# SCHEDA TECNICA



THIS DRAWING IS A CONTROLLED DOCUMENT. THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISIONS

REV.	DESCRIPTION	DATE	BY	CHK
NC	NEW RELEASE PER E.O. P18512			
A	REVISED PER E.O. P18815			
B	REVISED PER E.O. P18119			
C	REVISED PER ECO-14-019072			

SCALE 1:1

NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)  
 RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)  
 GROMMET: SILICONE (ORANGE-RED)

SEE 0425-021-0000 APPLICATION SPECIFICATION  
 A. RECOMMENDED WIRE INSULATION RANGE  
 B. CONTACT REMOVAL TOOLS

THIS PLUG MATES WITH HDP24-24XXP/SX-XXXX RECEPTACLE  
 X = SEAL TYPE (N, I, E)  
 XX = INSERT ARRANGEMENT  
 XXX = MODIFICATION

SEE CUSTOMER DRAWING 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

Customer Drawing: 0425-021-0000  
 DATE: 04/25/03  
 DRAWN BY: [Signature]  
 CHECKED BY: [Signature]  
 APPROVED BY: [Signature]

Customer Drawing: 0425-021-0000  
 DATE: 04/25/03  
 DRAWN BY: [Signature]  
 CHECKED BY: [Signature]  
 APPROVED BY: [Signature]

Customer Drawing: 0425-021-0000  
 DATE: 04/25/03  
 DRAWN BY: [Signature]  
 CHECKED BY: [Signature]  
 APPROVED BY: [Signature]