



THIS DRAWING IS A CONTROLLED DOCUMENT. THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISIONS

REV	DATE	DESCRIPTION	BY	CHK
A	15/03/2003	NEW RELEASE PER E.O. P168172	SG	BSM
B	15/03/2003	REVISIO PER E.O. P168175	SG	BSM
C	14/01/2012	REVISIO PER E.O. P168119	SG	BSM
C	14/01/2012	REVISIO PER E.O. P168172	SG	BSM

LOC: 2035

DATE: 15/03/2003

SCALE: 1:1

MAIN POLARIZING KEY

COUPLING RING

RETAINING HOUSING

PLUG MATES WITH HDP24-24XXP/SX-XXXX RECEPTACLE

Ø 1,950 (149,531 OVER HUBRL)

1,321±,025 (138,63±0,631)

Ø 1,470 (137,341)

Ø 1,470 (137,341)

DEUTSCH CONTACT INSERTION THIS SIDE

HDP26-24-XXP/SX

DATE CODE

POLARIZING INDICATOR

POLARIZING INDICATOR

GROMMET

NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)
 RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
 GROMMET: SILICONE (ORANGE-RED)

SEE 0425-021-0000 APPLICATION SPECIFICATION

A. RECOMMENDED WIRE INSULATION RANGE
 B. CONTACT REMOVAL TOOLS

5. NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

4. MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)
 RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
 GROMMET: SILICONE (ORANGE-RED)

3. SEE 0425-021-0000 APPLICATION SPECIFICATION
 A. RECOMMENDED WIRE INSULATION RANGE
 B. CONTACT REMOVAL TOOLS

2. THIS PLUG MATES WITH HDP24-24XXP/SX-XXXX RECEPTACLE
 X = SEAL TYPE (N, T, E)
 XX = INSERT ARRANGEMENT
 XXXX = MODIFICATION

1. SEE CUSTOMER DRAWING 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

NOTES:

THIS DRAWING IS A CONTROLLED DOCUMENT.

INCHES (MM)

CONTRACT NUMBER: 0425-021-0000

DATE: 15/03/2003

SCALE: 1:1

Customer Drawing

SCALE: 2-1

1 of 1

REV: C

DATE: 15/03/2003

BY: SG

CHK: BSM

DESCRIPTION: NEW RELEASE PER E.O. P168172

REVISED PER E.O. P168175

REVISED PER E.O. P168119

REVISED PER E.O. P168172

DATE CODE

DEUTSCH CONTACT INSERTION THIS SIDE

HDP26-24-XXP/SX

POLARIZING INDICATOR

POLARIZING INDICATOR

GROMMET

NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)
 RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
 GROMMET: SILICONE (ORANGE-RED)

SEE 0425-021-0000 APPLICATION SPECIFICATION

A. RECOMMENDED WIRE INSULATION RANGE
 B. CONTACT REMOVAL TOOLS

5. NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

4. MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)
 RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
 GROMMET: SILICONE (ORANGE-RED)

3. SEE 0425-021-0000 APPLICATION SPECIFICATION
 A. RECOMMENDED WIRE INSULATION RANGE
 B. CONTACT REMOVAL TOOLS

2. THIS PLUG MATES WITH HDP24-24XXP/SX-XXXX RECEPTACLE
 X = SEAL TYPE (N, T, E)
 XX = INSERT ARRANGEMENT
 XXXX = MODIFICATION

1. SEE CUSTOMER DRAWING 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

NOTES:

THIS DRAWING IS A CONTROLLED DOCUMENT.

INCHES (MM)

CONTRACT NUMBER: 0425-021-0000

DATE: 15/03/2003

SCALE: 1:1

Customer Drawing

SCALE: 2-1

1 of 1

REV: C