LOC	DIST
–	–

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED PER EO P15887	2-15-99	–	RDR
	B	REVISED PER EO P21310	4-26-12	RLM	RDR
	C	REVISED PER ECO-13-013634	8-26-13	RLM	DM
	C1	REVISED PER ECO-14-005288	4-9-14	PV	DM

OPTIONAL GATE VESTIGE
APPROX. AS SHOWN

CAVITY I.D. APPROX.
AS SHOWN.

.546
[13.87]

.498
[12.65]

.292
[7.42]

.244
[6.20]

OPTIONAL CONFIGURATION

SHORT TIP ONLY

.580
[14.73]

.545
[13.84]

1. USED WITH DT04-6P-**** (**** = ALL MODIFICATIONS).
   CONSULT FACTORY FOR MODIFICATIONS AND APPLICATION.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	R.MESSENGER	16AUG2013
CHK	R.MESSENGER	28MAR2014
APVD	D.MEYER	28MAR2014

TE TE Connectivity

DIMENSIONS:
INCHES[mm]

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±0.010 [0.25]
4 PLC	
ANGLES	±0°30'0"

PRODUCT SPEC
-

APPLICATION SPEC
-

NAME
WEDGE LOCK
6 WAY RECEPTACLE
DT SERIES

MATERIAL
PLASTIC
GREEN

FINISH
-

WEIGHT
0.84 g

| SIZE | CAGE CODE | DRAWING NO | | RESTRICTED TO |
| A3 | 4AFU8 | C=W6P | | |

CUSTOMER DRAWING

SCALE 4:1   SHEET 1 OF 1   REV C1

mes connettori
componenti per il cablaggio